




- For use to overcome situations where a rigid duct cannot be installed
- Recommended mainly for use with tumble dryers
- Suitable when there is slow moving air
- Available in four rectangular sizes and six round sizes
- PVC hose has a maximum working temperature of 80°C
- Aluminium duct options in 100, 125 and 150mm
- Round insulated aluminium hose available for condensation control
- A wide range of connectors, clips and tapes provide effective connections to rigid ducting systems and terminals




## DIMENSIONS


### Rectangular Hose




112 x 56mm (to connect to System 100 channel).



206 x 62mm (to connect to Supertube 125 channel).




222 x 92mm (to connect to MegaDuct 220 channel).




150 x 60mm (to fit 125mm round connections - ends form round for use where space prevents the flexible hose run being completely round).


### Round Hose



76mm, 89mm, 100mm, 125mm, 150mm diameters to fit EasiPipe and round connections



Insulated hose has an extra 25mm of insulation



200mm diameter hose (only available in PVC form).

Domus has a large range of round and rectangular PVC flexible hoses in various lengths that are compatible with System 100, Supertube 125, MegaDuct 220, EasiPipe and ThermaPipe. Hose provides solutions to overcome situations where a rigid component cannot be installed. Flexible hose is particularly suitable for installation where there is slow moving air, such as, the ducting of tumble dryers.







It is important when connected with higher volume appliances, like a cooker hood, that the hose should remain taut and in a straight line for optimum performance.

Also available is aluminium duct for use when extra strength is required and insulated aluminium hose that is suitable for whole-house ventilation, passive stack ventilation and air conditioning systems.




To complement the range of hoses and to ensure easy installation a selection of hose connectors, clips and tapes is available to provide effective connections.






## ROUND PVC FLEXIBLE HOSE

Product	Code		Length metres	Notes	Product	Code		Length metres	Notes
	Boxed	Prepack				Boxed	Prepack		
<b>76mm (3")</b> 	<b>261</b>	n/a	1	For use with adapters provided with many common tumble dryers.	<b>125mm (5")</b> 	<b>561</b>	n/a	1	Fits 125mm o.d. connections by using threaded hose connector (126-5). Alternatively use an adjustable hose clip (125-5).
	<b>263</b>	n/a	3			<b>563</b>	n/a	3	
	<b>266</b>	n/a	6			<b>566</b>	n/a	6	
	<b>2615</b>	n/a	15			<b>5615</b>	n/a	15	
<b>89mm (3.5")</b> 	<b>371</b>	n/a	1	For use with adapters provided with many common tumble dryers.	<b>150mm (6")</b> 	<b>661</b>	n/a	1	Fits 150mm o.d. connections by using threaded hose connector (126-6). Alternatively use an adjustable hose clip (125-6).
	<b>373</b>	n/a	3			<b>663</b>	n/a	3	
	<b>376</b>	n/a	6			<b>666</b>	n/a	6	
	<b>3715</b>	n/a	15			<b>6615</b>	n/a	15	
<b>100mm (4")</b> 	<b>361</b>	<b>40361</b>	1	Fits 100mm i.d. connections by using threaded hose connector (124-4) or to 100mm o.d. connections using connector (126-4). Alternatively use an adjustable hose clip (125-4).	<b>200mm (8")</b> 	<b>861</b>	n/a	1	Fits 200mm round connections by using adjustable hose clip (126-8).
	<b>363</b>	<b>40363</b>	3			<b>863</b>	n/a	3	
	<b>366</b>	n/a	6			<b>866</b>	n/a	6	
	<b>3615</b>	n/a	15			<b>866</b>	n/a	6	
	<b>3645</b>	n/a	45			<b>8615</b>	n/a	15	

## ROUND INSULATED HOSE

<b>100mm (4")</b> 	<b>4210</b>	n/a	10	Can be used in conjunction with ThermaPipe 100. Use aluminium duct sealing tape (50TP45) to seal joints.	<b>150mm (6")</b> 	<b>6210</b>	n/a	10	Can be used in conjunction with ThermaPipe 150. Use aluminium duct sealing tape (50TP45) to seal joints.
<b>125mm (5")</b> 	<b>5210</b>	n/a	10	Can be used in conjunction with ThermaPipe 125. Use aluminium duct sealing tape (50TP45) to seal joints.					













## ROUND ALUMINIUM DUCT

<b>100mm (4")</b> 	n/a	<b>403203</b>	0.3	Fits 100mm o.d. connections. Should be secured using duct clip (127-4).	<b>150mm (6")</b> 	n/a	<b>603203</b>	0.3	Fits 150mm o.d. connections. Should be secured using duct clip (127-6).
	n/a	<b>403215</b>	1.5			n/a	<b>603215</b>	1.5	
	n/a	<b>403230</b>	3			n/a	<b>603230</b>	3	
<b>125mm (5")</b> 	n/a	<b>503203</b>	0.3	Fits 125mm o.d. connections. Should be secured using duct clip (127-5).	Aluminium duct has a 15 minute fire rating. Maximum working temperature of 200°C.				
	n/a	<b>503215</b>	1.5						
	n/a	<b>503230</b>	3						









## ROUND HOSE ACCESSORIES

Product	Code		Description	Dimensions mm	Notes
	Boxed	Prepack			
<b>100mm (4")</b>     	<b>124-4</b>	<b>40124</b>	<b>Threaded Hose Connector with Spigot</b>	○ 100	Used to connect a length of 100mm PVC flexible hose to any item with a 100mm i.d. Provides professional finish.
	<b>126-4</b>	<b>40126</b>	<b>Threaded Hose Connector with Socket</b>	● 100	Used to connect a length of 100mm PVC flexible hose to any item with a 100mm o.d. Provides professional finish.
	<b>126-110</b>	<b>n/a</b>	<b>Threaded Hose Connector for 110mm Pipe</b>	● 110	Used to connect a length of 100mm PVC flexible hose to 110mm soil pipe. Provides professional finish.
	<b>125-4</b>	<b>40125*</b>	<b>Adjustable Round Hose Clip</b>	● 90 - 110	Used to connect a length of 100mm PVC flexible hose to any item with a 100mm o.d.
	<b>127-4</b>	<b>40127*</b>	<b>Adjustable Aluminium Duct Clip</b>	● 100 - 110	Used to to fasten a length of 100mm aluminium duct to 100mm o.d. connections.
<b>125mm (5")</b>   	<b>126-5</b>	<b>n/a</b>	<b>Threaded Hose Connector with Socket</b>	● 125	Used to connect a length of 125mm PVC flexible hose to any item with a 125mm o.d. Provides professional finish.
	<b>125-5</b>	<b>n/a</b>	<b>Adjustable Round Hose Clip</b>	● 120 - 140	Used to connect a length of 125mm PVC flexible hose to any item with a 125mm o.d.
	<b>127-5</b>	<b>n/a</b>	<b>Adjustable Aluminium Duct Clip</b>	● 125 - 135	Used to to fasten a length of 125mm aluminium duct to 125mm o.d. connections.
<b>150mm (6")</b>   	<b>126-6</b>	<b>n/a</b>	<b>Threaded Hose Connector with Socket</b>	● 150	Used to connect a length of 150mm PVC flexible hose to any item with a 150mm o.d. Provides professional finish.
	<b>125-6</b>	<b>n/a</b>	<b>Adjustable Round Hose Clip</b>	● 140 - 160	Used to connect a length of 150mm PVC flexible hose to any item with a 150mm o.d.
	<b>127-6</b>	<b>n/a</b>	<b>Adjustable Aluminium Duct Clip</b>	● 150 - 160	Used to to fasten a length of 150mm aluminium duct to 150mm o.d. connections.
<b>200mm (8")</b> 	<b>125-8</b>	<b>n/a</b>	<b>Adjustable Hose Clip</b>	● 65 - 215	Mainly used to connect a length of 200mm PVC flexible hose to any item with a 200mm o.d. However, this can be reduced to 65mm and is therefore suitable for 76 & 89mm flexi hose.





\* Contains 2 items in retail pack    ● = internal dimension    ○ = outer dimension



## RECTANGULAR PVC FLEXIBLE HOSE

Product	Code		Length metres	Notes	Product	Code		Length metres	Notes
	Boxed	Prepack				Boxed	Retail		
<b>112 x 56mm</b> 	<b>3305</b> <b>333</b>	<b>40335</b> <b>n/a</b>	0.5 3	Slips over System 100 channel secured by PVC duct tape (123/123-4).	<b>150 x 60mm</b> 	<b>5505</b> <b>5533</b>	<b>n/a</b> <b>n/a</b>	0.5 3	For use with EasiPipe 125. Allows greater flexibility when space is a restriction. Hose forms round to fit 125mm connections, eg wall outlets.
<b>206 x 62mm</b> 	<b>5305</b> <b>533</b>	<b>n/a</b> <b>n/a</b>	0.5 3	Slips over Supertube 125 channel secured by PVC duct tape (123/123-4).	<b>222 x 92mm</b> 	<b>9305</b> <b>933</b>	<b>n/a</b> <b>n/a</b>	0.5 3	Slips over MegaDuct 220 channel secured by PVC duct tape (123/123-4).

## RECTANGULAR FLEXIBLE HOSE ACC.

Product	Code		Description	Dimensions mm	Notes
	Boxed	Prepack			
	<b>381</b>	<b>n/a</b>	Rectangular Hose Connector 100mm length	□ 110 x 54	Used to connect two pieces of System 100 rectangular hose. Tape joints with duct sealing tape.
	<b>581</b>	<b>n/a</b>	Rectangular Hose Connector 100mm length	□ 204 x 60	Used to connect two pieces of Supertube 125 rectangular hose. Tape joints with duct sealing tape.
	<b>123-4</b>	<b>40123</b>	PVC Duct Sealing Tape	4.6m length 50mm wide	To secure rectangular flexible hose to channels or for sealing any duct joint to ensure an airtight connection.
	<b>123</b>	<b>n/a</b>	PVC Duct Sealing Tape	33m length 50mm wide	To secure rectangular flexible hose to channels or for sealing any duct joint to ensure an airtight connection.

□ = outer dimension

