



## SOKI 6 and 7 plus solar compact installations

The solar compact installation enables the heat transfer medium to be circulated in the solar circuit between the collector and the cylinder heat exchanger. It is equipped with a solar control unit. In connection with the SOKI SAS cylinder connection set, it can be fitted directly to the SBB .. plus cylinder. Power supply cable with plug and cylinder sensor are factory-fitted. It is provided with thermal insulation to minimise heat losses. An integral non-return valve prevents the undesirable thermo-siphon effect, i.e. the solar cylinder does not lose its heat when the circulation pump is idle. The flow rate can be checked and regulated at any time. A safety valve, indicator thermometer for flow and return, system air vent valve, shut-off valves for flushing, filling and draining the system, connection for an expansion vessel and a wall retainer are included.



### The most important features

Appealing design

Up to 16 SOL 27 plus, SOL 20 plus or SOL 23 plus collectors can be used

With system air vent valve

These devices are fully wired

The SOKI 6 plus is equipped with an integral SOM 6 plus solar control unit

The SOKI 7 plus is equipped with a SOM 7 plus solar control unit



Type		
Type	SOKI 6 plus	SOKI 7 plus
Part no.	220459	220460
Weight	5,90 kg	5,90 kg

Specification		
Height	500 mm	500 mm
Width	285 mm	285 mm
Depth	162 mm	162 mm
Flow meter display	1-13 l/min	1-13 l/min
Heat meter	No	Yes
Power consumption	44/63/82 W	44/63/82 W
Expansion vessel connection	G 3/4 male	G 3/4 male